



NYS225

Mono 2 pole plug with anti-kink boot and large metal handle for speaker cables









Article Variations

Article Name	Details	Packaging
NYS225	silvery handle	
NYS225B	black handle	
NYS225L	silvery handle, large cable outlet (9 mm)	
NYS225S	silvery handle, tip switched to ground if not inserted (silent) for guitar cables	



Technical Information

Product		
Title	NYS225	
Connection Type	1/4" Plugs & Jacks	

Electrical		
Contact Resistance	≤ 10mΩ	
Insulation Resistance	≥ 200 MΩ(Initial)	
Dielectric Strength	0.5 KVdc 50HZ	

Mechanical		
Lifetime	> 1,000 Mating Cycles	
Insertion and Withdrawal Force	≤ 60 N	
Cable O.D.	max 8.8 mm for standard outlet max 10 mm for large outlet (* L)	
Wiresize	12 AWG	



Material		
Tip	Brass	
Bushing	PA66+30%GF	
Inner	Steel	
Insulation	CerPVC	
Sleeve	Brass	
Sleeve		
Insulation	PA66+30%GF	
Soldering Contact	Brass	
Cable Clamp	Steel	
Housing	Zinc	
Push Ring	ABS	
Boot	CerPVC	
Tip	Nickel Plating	
Sleeve	Nickel Plating	
Sleeve	Nickel Plating	
Housing	Nickel Plating	
Inner	Zinc Plating	
Soldering Contact	Tin and Cer	
Cable Clamp	Tin and Cer	